


Ruland Manufacturing Disc couplings Ruland Manufacturing

SKU: 610MDCS411813A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	41.3
Gewicht (kg)	0.2521
boreDiameterTol	+0.03 mm / -0.00 mm
nmax(rpm)	10000
boreB1Mm	18
boreB2Mm	13
lenghtLInch	1.563
lenghtLMm	39.7
AngularMisalignmentDeg	1
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	4.6
UPC	634529151778
TariffCode	8483.60.8000

outsideDiameterInInput	1.625
ForgedClampScrew	M4
NumberofScrewsEa	2
FinishSpecification	Anodize
Style	Clamp
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	$2.791 \times 10^{-5} \text{ kg-m}^2$
StaticTorqueInput	20.3 Nm
NonReversingTorqueInput	10.15 Nm
ReversingTorqueInput	5.08 Nm
TorsionalStiffnessInput	70.6 Nm/Deg
ParallelMisalignmentInch	0.00 mm
AxialMotionInput	0.25 mm
Bore1ShaftPenetrationInput	19.2 mm
UNSPC	31163008
couplingType	Single
Bore2ShaftPenetrationInput	19.2 mm
Merk	Ruland Manufacturing

Beschrijving

Ruland Manufacturing Disc couplings

Product URL

<https://aandrijftechniek.nl/product/ruland-manufacturing-disc-couplings-ruland-manufacturing-1528/>