

DCS36-16-16-A Ruland Manufacturing Disc couplings Ruland Manufacturing

SKU: 610DCS361616A



Extra afbeelding



Specificaties

| | |
|-------------------------------|-------------------------|
| Materiaal | Aluminium |
| Buitendiameter (mm) | 57.2 |
| Gewicht (kg) | 0.6739 |
| boreDiameterTol | +0.001 in / -0.000 in |
| nmax(rpm) | 10000 |
| lenghtLInch | 2.313 |
| lenghtLMm | 58.8 |
| AngularMisalignmentDeg | 1 |
| couplingShaftTolerance | +0.0000 in / -0.0005 in |
| ScrewType | Alloy Steel |
| ScrewFinish | Black Oxide |
| SeatingTorqueNm | 16 |
| UPC | 634529091562 |
| TariffCode | 8483.60.8000 |
| boreB1Inch | 1.0000 in |

| | |
|-----------------------------------|--------------------------|
| outsideDiameterInInput | 2.25 |
| ForgedClampScrew | M6 |
| NumberofScrewsEa | 2 |
| FinishSpecification | Anodize |
| Style | Clamp |
| FasteningDimensions | Metric |
| ISO 9001 (2008) | Yes |
| REACH | Yes |
| ROHS2 | Yes |
| ConflictMinerals | Yes |
| MomentofInertia | 0.5048 lb-in² |
| boreB2Inch | 1.0000 |
| StaticTorqueInput | 450 lb-in |
| NonReversingTorqueInput | 225 lb-in |
| ReversingTorqueInput | 112.5 lb-in |
| TorsionalStiffnessInput | 1000 lb-in/Deg |
| ParallelMisalignmentInch | 0.00 in |
| AxialMotionInput | 0.015 in |
| Bore1ShaftPenetrationInput | 1.085 in |
| UNSPC | 31163008 |
| couplingType | Single |
| Bore2ShaftPenetrationInput | 1.085 in |
| Merk | Ruland Manufacturing |

Beschrijving

Ruland Manufacturing Disc couplings

Product URL

<https://aandrijftechniek.nl/product/ruland-manufacturing-disc-couplings-ruland-manufacturing-1545/>