


# Ruland Manufacturing Disc couplings Ruland Manufacturing

SKU: 610DCS1654A



## Extra afbeelding



## Specificaties

|                               |                         |
|-------------------------------|-------------------------|
| <b>Materiaal</b>              | Aluminium               |
| <b>Buitendiameter (mm)</b>    | 25.4                    |
| <b>Gewicht (kg)</b>           | 0.0655                  |
| <b>boreDiameterTol</b>        | +0.001 in / -0.000 in   |
| <b>nmax(rpm)</b>              | 10000                   |
| <b>lenghtLInch</b>            | 1.031                   |
| <b>lenghtLMm</b>              | 26.2                    |
| <b>AngularMisalignmentDeg</b> | 1                       |
| <b>couplingShaftTolerance</b> | +0.0000 in / -0.0005 in |
| <b>ScrewType</b>              | Alloy Steel             |
| <b>ScrewFinish</b>            | Black Oxide             |
| <b>SeatingTorqueNm</b>        | 2.1                     |
| <b>UPC</b>                    | 634529082188            |
| <b>TariffCode</b>             | 8483.60.8000            |
| <b>boreB1Inch</b>             | 0.3125                  |
| <b>outsideDiameterInInput</b> | 1                       |

|                                   |                           |
|-----------------------------------|---------------------------|
| <b>ForgedClampScrew</b>           | M3                        |
| <b>NumberofScrewsEa</b>           | 2                         |
| <b>FinishSpecification</b>        | Anodize                   |
| <b>Style</b>                      | Clamp                     |
| <b>FasteningDimensions</b>        | Metric                    |
| <b>ISO 9001 (2008)</b>            | Yes                       |
| <b>REACH</b>                      | Yes                       |
| <b>ROHS2</b>                      | Yes                       |
| <b>ConflictMinerals</b>           | Yes                       |
| <b>MomentofInertia</b>            | 0.0089 lb-in <sup>2</sup> |
| <b>boreB2Inch</b>                 | 0.2500                    |
| <b>StaticTorqueInput</b>          | 50 lb-in                  |
| <b>NonReversingTorqueInput</b>    | 25 lb-in                  |
| <b>ReversingTorqueInput</b>       | 12.5 lb-in                |
| <b>TorsionalStiffnessInput</b>    | 94 lb-in/Deg              |
| <b>ParallelMisalignmentInch</b>   | 0.00 in                   |
| <b>AxialMotionInput</b>           | 0.006 in                  |
| <b>Bore1ShaftPenetrationInput</b> | 0.499 in                  |
| <b>UNSPC</b>                      | 31163008                  |
| <b>couplingType</b>               | Single                    |
| <b>Bore2ShaftPenetrationInput</b> | 0.499 in                  |
| <b>Merk</b>                       | Ruland Manufacturing      |

## Beschrijving

Ruland Manufacturing Disc couplings

## Product URL

<https://aandrijftechniek.nl/product/ruland-manufacturing-disc-couplings-ruland-manufacturing-182/>