

Ruland Manufacturing Disc couplings Ruland Manufacturing

SKU: 610DCS2688A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	41.3
Gewicht (kg)	0.2677
boreDiameterTol	+0.001 in / -0.000 in
nmax(rpm)	10000
lenghtLinch	1.563
lenghtLMm	39.7
AngularMisalignmentDeg	1
couplingShaftTolerance	+0.0000 in / -0.0005 in
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	4.6
UPC	634529082461
TariffCode	8483.60.8000
boreB1Inch	0.5000
outsideDiameterInInput	1.625

ForgedClampScrew	M4
NumberofScrewsEa	2
FinishSpecification	Anodize
Style	Clamp
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	0.0967 lb-in ²
boreB2Inch	0.5000
StaticTorqueInput	180 lb-in
NonReversingTorqueInput	90 lb-in
ReversingTorqueInput	45 lb-in
TorsionalStiffnessInput	625 lb-in/Deg
ParallelMisalignmentInch	0.00 in
AxialMotionInput	0.010 in
Bore1ShaftPenetrationInput	0.755 in
UNSPC	31163008
couplingType	Single
Bore2ShaftPenetrationInput	0.755 in
Merk	Ruland Manufacturing

Beschrijving

Ruland Manufacturing Disc couplings

Product URL

<https://aandrijftechniek.nl/product/ruland-manufacturing-disc-couplings-ruland-manufacturing-195/>