

Ruland Manufacturing Disc couplings Ruland Manufacturing

SKU: 610DCS32128A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	50.8
Gewicht (kg)	0.4644
boreDiameterTol	+0.001 in / -0.000 in
nmax(rpm)	10000
lenghtLInch	1.813
lenghtLMm	46.1
AngularMisalignmentDeg	1
couplingShaftTolerance	+0.0000 in / -0.0005 in
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	9.5
UPC	634529082515
TariffCode	8483.60.8000
boreB1Inch	0.7500
outsideDiameterInInput	2

ForgedClampScrew	M5
NumberofScrewsEa	2
FinishSpecification	Anodize
Style	Clamp
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	0.2550 lb-in ²
boreB2Inch	0.5000
StaticTorqueInput	350 lb-in
NonReversingTorqueInput	175 lb-in
ReversingTorqueInput	87.5 lb-in
TorsionalStiffnessInput	867 lb-in/Deg
ParallelMisalignmentInch	0.00 in
AxialMotionInput	0.012 in
Bore1ShaftPenetrationInput	0.874 in
UNSPC	31163008
couplingType	Single
Bore2ShaftPenetrationInput	0.874 in
Merk	Ruland Manufacturing

Beschrijving

Ruland Manufacturing Disc couplings

Product URL

<https://aandrijftechniek.nl/product/ruland-manufacturing-disc-couplings-ruland-manufacturing-216/>