

MDCD19-7-4-A Ruland Manufacturing Disc couplings Ruland Manufacturing

SKU: 610MDCD1974A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	19.1
Gewicht (kg)	0.0426
boreDiameterTol	+0.03 mm / -0.00 mm
nmax(rpm)	10000
boreB1Mm	7
boreB2Mm	4
lenghtLInch	1.189
lenghtLMm	30.2
AngularMisalignmentDeg	2
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	1.21
UPC	634529208571

TariffCode	8483.60.8000
outsideDiameterInInput	0.75
ForgedClampScrew	M2.5
NumberofScrewsEa	2
FinishSpecification	Anodize
Style	Clamp
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	$9.590 \times 10^{-7} \text{ kg-m}^2$
StaticTorqueInput	2.8 Nm
NonReversingTorqueInput	1.40 Nm
ReversingTorqueInput	0.70 Nm
TorsionalStiffnessInput	5.8 Nm/Deg
ParallelMisalignmentInch	0.10 mm
AxialMotionInput	0.20 mm
Bore1ShaftPenetrationInput	14.6 mm
UNSPC	31163008
couplingType	Double
Bore2ShaftPenetrationInput	14.6 mm
Merk	Ruland Manufacturing

Beschrijving

Ruland Manufacturing Disc couplings

Product URL

<https://aandrijftechniek.nl/product/ruland-manufacturing-disc-couplings-ruland-manufacturing-237/>