

Ruland Manufacturing Disc couplings Ruland Manufacturing

SKU: 610MDCD572819A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	57.2
Gewicht (kg)	0.876
boreDiameterTol	+0.03 mm / -0.00 mm
nmax(rpm)	10000
boreB1Mm	28
boreB2Mm	19
lenghtLInch	3.08
lenghtLMm	78.2
AngularMisalignmentDeg	2
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	16
UPC	634529137444
TariffCode	8483.60.8000

outsideDiameterInInput	2.25
ForgedClampScrew	M6
NumberofScrewsEa	2
FinishSpecification	Anodize
Style	Clamp
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	1.922 x 10 ⁻⁴ kg-m ²
StaticTorqueInput	50.9 Nm
NonReversingTorqueInput	25.45 Nm
ReversingTorqueInput	12.73 Nm
TorsionalStiffnessInput	86.9 Nm/Deg
ParallelMisalignmentInch	0.30 mm
AxialMotionInput	0.76 mm
Bore1ShaftPenetrationInput	37.0 mm
UNSPC	31163008
couplingType	Double
Bore2ShaftPenetrationInput	37.0 mm
Merk	Ruland Manufacturing

Beschrijving

Ruland Manufacturing Disc couplings

Product URL

<https://aandrijftechniek.nl/product/ruland-manufacturing-disc-couplings-ruland-manufacturing-463/>