


Ruland Manufacturing Disc couplings Ruland Manufacturing

SKU: 610MDCDE2566A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	25.4
Gewicht (kg)	0.0785
boreDiameterTol	+0.03 mm / -0.00 mm
nmax(rpm)	10000
boreB1Mm	6
boreB2Mm	6
lenghtLInch	1.374
lenghtLMm	34.9
AngularMisalignmentDeg	2
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	2.1
UPC	634529089415
TariffCode	8483.60.8000

outsideDiameterInInput	1
ForgedClampScrew	M3
NumberofScrewsEa	2
FinishSpecification	Anodize
Style	Clamp
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	3.117 x 10 ⁻⁶ kg-m ²
StaticTorqueInput	5.6 Nm
NonReversingTorqueInput	2.80 Nm
ReversingTorqueInput	1.40 Nm
TorsionalStiffnessInput	6.9 Nm/Deg
ParallelMisalignmentInch	0.15 mm
AxialMotionInput	0.30 mm
Bore1ShaftPenetrationInput	16.6 mm
UNSPC	31163008
couplingType	Double
Bore2ShaftPenetrationInput	16.6 mm
Merk	Ruland Manufacturing

Beschrijving

Ruland Manufacturing Disc couplings

Product URL

<https://aandrijftechniek.nl/product/ruland-manufacturing-disc-couplings-ruland-manufacturing-499/>