

Ruland Manufacturing Disc couplings Ruland Manufacturing

SKU: 610MDCDK411911A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	41.3
Gewicht (kg)	0.3052
boreDiameterTol	+0.03 mm / -0.00 mm
nmax(rpm)	10000
boreB1Mm	19
boreB2Mm	11
lenghtLInch	2.165
lenghtLMm	55
AngularMisalignmentDeg	2
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	4.6
UPC	634529175736
TariffCode	8483.60.8000

outsideDiameterInInput	1.625
ForgedClampScrew	M4
NumberofScrewsEa	2
FinishSpecification	Anodize
Style	Clamp
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	3.7901 x 10 ⁻⁵ kg-m ²
Keyway(K1)	6 mm
Keyway(K2)	4 mm
StaticTorqueInput	20.3 Nm
NonReversingTorqueInput	10.15 Nm
ReversingTorqueInput	5.08 Nm
TorsionalStiffnessInput	42.4 Nm/Deg
ParallelMisalignmentInch	0.25 mm
AxialMotionInput	0.51 mm
Bore1ShaftPenetrationInput	26.1 mm
UNSPC	31163008
couplingType	Double
Bore2ShaftPenetrationInput	26.1 mm
Merk	Ruland Manufacturing

Beschrijving

Ruland Manufacturing Disc couplings

Product URL

<https://aandrijftechniek.nl/product/ruland-manufacturing-disc-couplings-ruland-manufacturing-652/>