


Ruland Manufacturing Disc couplings Ruland Manufacturing

SKU: 610MDCDK511914A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	50.8
Gewicht (kg)	0.6023
boreDiameterTol	+0.03 mm / -0.00 mm
nmax(rpm)	10000
boreB1Mm	19
boreB2Mm	14
lenghtLInch	2.519
lenghtLMm	64
AngularMisalignmentDeg	2
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	9.5
UPC	634529176986
TariffCode	8483.60.8000

outsideDiameterInInput	2
ForgedClampScrew	M5
NumberofScrewsEa	2
FinishSpecification	Anodize
Style	Clamp
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	1.0041 x 10 ⁻⁴ kg-m ²
Keyway(K1)	6 mm
Keyway(K2)	5 mm
StaticTorqueInput	39.6 Nm
NonReversingTorqueInput	19.80 Nm
ReversingTorqueInput	9.90 Nm
TorsionalStiffnessInput	67.2 Nm/Deg
ParallelMisalignmentInch	0.30 mm
AxialMotionInput	0.64 mm
Bore1ShaftPenetrationInput	30.3 mm
UNSPC	31163008
couplingType	Double
Bore2ShaftPenetrationInput	30.3 mm
Merk	Ruland Manufacturing

Beschrijving

Ruland Manufacturing Disc couplings

Product URL

<https://aandrijftechniek.nl/product/ruland-manufacturing-disc-couplings-ruland-manufacturing-707/>