

Ruland Manufacturing Disc couplings Ruland Manufacturing

SKU: 610MDCS1553A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	15
Gewicht (kg)	0.0162
boreDiameterTol	+0.03 mm / -0.00 mm
nmax(rpm)	10000
boreB1Mm	5
boreB2Mm	3
lenghtLInch	0.719
lenghtLMm	18.3
AngularMisalignmentDeg	0.5
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	0.6
UPC	634529084724
TariffCode	8483.60.8000

outsideDiameterInInput	0.59
ForgedClampScrew	M2
NumberofScrewsEa	2
FinishSpecification	Anodize
Style	Clamp
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	$2.250 \times 10^{-7} \text{ kg-m}^2$
StaticTorqueInput	1.7 Nm
NonReversingTorqueInput	0.85 Nm
ReversingTorqueInput	0.43 Nm
TorsionalStiffnessInput	5.6 Nm/Deg
ParallelMisalignmentInch	0.00 mm
AxialMotionInput	0.05 mm
Bore1ShaftPenetrationInput	9.0 mm
UNSPC	31163008
couplingType	Single
Bore2ShaftPenetrationInput	9.0 mm
Merk	Ruland Manufacturing

Beschrijving

Ruland Manufacturing Disc couplings

Product URL

<https://aandrijftechniek.nl/product/ruland-manufacturing-disc-couplings-ruland-manufacturing-775/>