

Ruland Manufacturing Disc couplings Ruland Manufacturing

SKU: 610MDCS331613A



Extra afbeelding



Specificaties

Materiaal	Aluminium
Buitendiameter (mm)	33.3
Gewicht (kg)	0.1268
boreDiameterTol	+0.03 mm / -0.00 mm
nmax(rpm)	10000
boreB1Mm	16
boreB2Mm	13
lenghtLInch	1.313
lenghtLMm	33.3
AngularMisalignmentDeg	1
couplingShaftTolerance	+0.000 mm / -0.013 mm
ScrewType	Alloy Steel
ScrewFinish	Black Oxide
SeatingTorqueNm	2.1
UPC	634529210512
TariffCode	8483.60.8000

outsideDiameterInInput	1.313
ForgedClampScrew	M3
NumberofScrewsEa	2
FinishSpecification	Anodize
Style	Clamp
FasteningDimensions	Metric
ISO 9001 (2008)	Yes
REACH	Yes
ROHS2	Yes
ConflictMinerals	Yes
MomentofInertia	$9.444 \times 10^{-6} \text{ kg-m}^2$
StaticTorqueInput	11.3 Nm
NonReversingTorqueInput	5.65 Nm
ReversingTorqueInput	2.83 Nm
TorsionalStiffnessInput	35.4 Nm/Deg
ParallelMisalignmentInch	0.00 mm
AxialMotionInput	0.20 mm
Bore1ShaftPenetrationInput	15.0 mm
UNSPC	31163008
couplingType	Single
Bore2ShaftPenetrationInput	16.1 mm
Merk	Ruland Manufacturing

Beschrijving

Ruland Manufacturing Disc couplings

Product URL

<https://aandrijftechniek.nl/product/ruland-manufacturing-disc-couplings-ruland-manufacturing-822/>