

## SP-28-A Ruland Manufacturing Shaft collar Ruland Manufacturing

SKU: 610SP28A



### Extra afbeelding



### Specificaties

|                               |                                |
|-------------------------------|--------------------------------|
| <b>Gewicht (kg)</b>           | 0.1159                         |
| <b>boreType</b>               | Round                          |
| <b>OriginalType</b>           | Shaft Collar - Two-Piece Split |
| <b>SteelMaterial</b>          | Aluminum                       |
| <b>UNSPSCcode</b>             | 31162811                       |
| <b>MaterialSpecification</b>  | 2024-T351 Bar                  |
| <b>ScrewType</b>              | Alloy Steel                    |
| <b>ScrewFinish</b>            | Black Oxide                    |
| <b>UPC</b>                    | 634529020951                   |
| <b>TariffCode</b>             | 8483.60.8000                   |
| <b>boreB1Inch</b>             | 1.75                           |
| <b>outsideDiameterInInput</b> | 2.75                           |
| <b>widthWInchInput</b>        | 0.688                          |
| <b>ClearanceDiameterInch</b>  | 3.046                          |
| <b>ForgedClampScrew</b>       | 5/16-24                        |
| <b>NumberofScrewsEa</b>       | 2                              |

|                            |                         |
|----------------------------|-------------------------|
| <b>ScrewLocation??</b>     | 1.125 in                |
| <b>WidthTolerance</b>      | +0.003 in / -0.010 in   |
| <b>BoreTolerance</b>       | +0.0020 in / +0.0005 in |
| <b>SeatingTorque</b>       | 325 lb-in               |
| <b>FinishSpecification</b> | Bright No Plating       |
| <b>BoreStyle</b>           | Round                   |
| <b>Style</b>               | Clamp                   |
| <b>ShaftTolerance</b>      | +0.0000 in / -0.0005 in |
| <b>FasteningDimensions</b> | Inch                    |
| <b>ISO 9001 (2008)</b>     | Yes                     |
| <b>REACH</b>               | Yes                     |
| <b>ROHS2</b>               | Yes                     |
| <b>ConflictMinerals</b>    | Yes                     |
| <b>RecommendedGap</b>      | 0.125 in                |
| <b>Merk</b>                | Ruland Manufacturing    |

## Beschrijving

SP-28-A Ruland Manufacturing Shaft collar

## Product URL

<https://aandrijftechniek.nl/product/sp-28-a-ruland-manufacturing-shaft-collar-ruland-manufacturing/>