

SPC3350/6 GATES Super HC™ Powerband™ Banded V-belts GATES

SKU: 4G000SPC3350/6

Specificaties

| | |
|--------------------------------------|----------------|
| Gewicht (kg/m) | 8.886 |
| Type riem | Narrow wrapped |
| Buitenlengte (mm) | 3380 |
| Hoogte riem (mm) | 18 |
| Breedte riem (mm) | 132 |
| Standaard | DIN/ISO |
| Minimale diameter pulley (mm) | 224 |
| Antistatisch | Nee |
| Binnenlengte (mm) | 3273 |
| Spoorlengte (mm) | 3350 |
| Materiaal riem | Chloroprene |
| Koordmateriaal | Polyester |
| Eenheden | pc |
| Riemprofiel | SPC |
| Ribsteek (S) (mm) | 25.5 |
| Ribbreedte riem (mm) | 6 |
| Gewicht (kg) | 8.886 |

| | |
|----------------------------------|---|
| Omschrijving (EN) | When uptime is a must, equip your drives with Gates® Super HC™ PowerBand™ belts. Super HC™ PowerBand™ belts offer a solution for drives where single belts vibrate, turn over or jump off the pulleys. With a superior combination of flex and load, the PowerBand™ construction consists of multiple V-belts joined together by a permanent, high strength tie band that functions as a single unit. This means a tougher, more stable solution with even load distribution and each strand fitting securely in the sheave groove. Highly resistant to tensile and flexing forces, fatigue and shock loads. High stability and smooth running on the toughest drives. Temperature Range: -30°C to +60°C (-22°F to +140°F). |
| Minimale temperatuur (°C) | -30 |
| Maximale temperatuur (°C) | +60 |
| EAN-code | 5412571081664 |
| Aangepaste code | 4010.3900.90 |
| numberOfRibs | 6 |
| Status | Normal |
| oringColour | BLACK |
| Land van herkomst | PL |
| Constructie | Bandless |
| beltInside | Smooth |
| beltBackSide | Smooth |
| Hoek | 40 |
| Bereik/ROHS-conformiteit | REACH and RoHS 2 |
| ISO1-standaard | 1813 |
| Merk | GATES |

Beschrijving

SPC3350/6 GATES Super HC™ Powerband™ Banded V-belts

Product URL

<https://aandrijftechniek.nl/product/spc3350-6-gates-super-hc-powerband-banded-v-belts-gates/>