

SPCP3150/2 GATES Predator™ Powerband™ Banded V-belts GATES

SKU: 4G000SPC3150/2P

Specificaties

Gewicht (kg/m)	2.923
Type riem	Narrow wrapped
Buitenlengte (mm)	3180
Hoogte riem (mm)	18
Breedte riem (mm)	44
Standaard	DIN/ISO
Minimale diameter pulley (mm)	224
Antistatisch	Nee
Binnenlengte (mm)	3073
Spoorlengte (mm)	3150
Materiaal riem	Chloroprene
Koordmateriaal	Aramid
Eenheden	pc
Riemprofiel	SPCP
Ribsteek (S) (mm)	25.5
Ribbreedte riem (mm)	2
Gewicht (kg)	2.923

Omschrijving (EN)	Gates' Predator™ PowerBand™ belt design offers a solution for drives where single belts vibrate, turn over or jump off the pulleys. It consists of several V-belts joined together by a permanent, high-strength tie band allowing the belts to work together as one unit. The Predator™ Powerband™ belt is especially designed for demanding applications and harsh environments and offers a high resistance to vibration. Specifically designed for high-demand applications, the extra heavy-duty belt construction provides extraordinary high impact strength, capacity and wear resistance. Aramid Tensile Cords combine limited stretch with extraordinary strength and durability that is pound-for-pound stronger than steel. Bareback Cover resists debris and allows the belt to slip under extreme shock load conditions, reducing heat build-up and prolonging belt life. Multiple layer Tie Band provides excellent lateral rigidity to prevent belts from turning over or from coming off of the drive.
Minimale temperatuur (°C)	-30
Maximale temperatuur (°C)	+60
EAN-code	5414465585586
Aangepaste code	4010.3900.90
numberOfRibs	2
Status	Normal
oringColour	BLACK
Land van herkomst	PL
Constructie	Bandless
beltInside	Smooth
beltBackSide	Smooth
Hoek	40
Bereik/ROHS-conformiteit	REACH and RoHS 2
ISO1-standaard	1813
Merk	GATES

Beschrijving

SPCP3150/2 GATES Predator™ Powerband™ Banded V-belts

Product URL

<https://aandrijftechniek.nl/product/spcp3150-2-gates-predator-powerband-banded-v-belts-gates/>