

SPZ1637MN GATES Super HC™ Molded Notch Endless V-belts GATES

SKU: 4G000SPZ1537MN



Specificaties

Gewicht (kg/m)	0.119
Type riem	Narrow raw edge
Geschikt voor automotive	Ja
Profiel	SPZ
Buitenlengte (mm)	1650
Hoogte riem (mm)	8
Breedte riem (mm)	10
Standaard	DIN7753
Minimale diameter pulley (mm)	63
Antistatisch	Nee
Binnenlengte (mm)	1599
Spoorlengte (mm)	1637
Materiaal riem	Chloroprene
Koordmateriaal	Polyester

Eenheden	pc
Riemprofiel	SPZMN
Gewicht (kg)	0.119
Omschrijving (EN)	<p>When your power transmission application needs a high horsepower solution but is constrained by drive weight or physical space, the answer is Super HC™ Moulded Notch Belts. Our proprietary construction process provides a superior combination of flex and load-carrying capacity, transmitting up to three times the horsepower versus comparably sized belts. Super HC™ MN V-belts put more power where high speeds, high speed ratios or small pulley diameters are required, offering significant benefits over classical section V-belts. Developed through specialised research, Super HC™ MN is highly recommended for use on all industrial heavy-duty, narrow section V-belt drives. With an increased transmission efficiency this belt allows for a more compact and highly economical drive design. Flex-bonded tensile cords are vulcanized as one solid unit making the belt highly resistant to tensile and flexing forces, fatigue and shock loads. Precision-ground straight sidewalls give a uniform wedging action and ensure the belt fits correctly in the pulley grooves, which improves belt life and reduces expensive maintenance time. Cost and space savings by reducing size of pulleys, bearings, guards and mounts.</p>
Minimale temperatuur (°C)	-30
Maximale temperatuur (°C)	+60
EAN-code	5412571108941
Aangepaste code	4010.3200.00
numberOfRibs	1
Status	Normal
oringColour	BLACK
Land van herkomst	FR
Constructie	Bandless
beltInside	Notched
beltBackSide	Smooth
Hoek	42
Bereik/ROHS-conformiteit	REACH and RoHS 2
ISO1-standaard	1813
Merk	GATES
Gewicht (kg/m)	0.119
Profiel	SPZ

Buitenlengte (mm)	1650
Breedte riem (mm)	10
Antistatisch	Nee
Binnenlengte (mm)	1599
Materiaal riem	Chloroprene
Riemprofiel	SPZMN
Gewicht (kg)	0.119
Minimale temperatuur (°C)	-30
Maximale temperatuur (°C)	+60
Land van herkomst	FR

Beschrijving

SPZ1637MN GATES Super HC™ Molded Notch Endless V-belts

Product URL

<https://aandrijftechniek.nl/product/spz1637mn-gates-super-hc-molded-notch-endless-v-belts-gates/>