

# TCL-3-32-SS Ruland Manufacturing Shaft collar Ruland Manufacturing

SKU: 610TCL332SS



## Extra afbeelding



## Specificaties

|                               |                                 |
|-------------------------------|---------------------------------|
| <b>Gewicht (kg)</b>           | 0.0094                          |
| <b>boreType</b>               | Right Threaded (Standard)       |
| <b>OriginalType</b>           | Shaft Collar - Threaded (Right) |
| <b>SteelMaterial</b>          | 303 Stainless Steel             |
| <b>UNSPSCcode</b>             | 31162811                        |
| <b>MaterialSpecification</b>  | 303 Stainless Steel             |
| <b>ScrewType</b>              | 18-8 300 Series Stainless Steel |
| <b>ScrewFinish</b>            | Bright                          |
| <b>UPC</b>                    | 634529028346                    |
| <b>TariffCode</b>             | 8483.60.8000                    |
| <b>outsideDiameterInInput</b> | 5/8                             |
| <b>widthWInchInput</b>        | 0.281                           |
| <b>ClearanceDiameterInch</b>  | 0.773                           |
| <b>ForgedClampScrew</b>       | #4-40                           |
| <b>NumberofScrewsEa</b>       | 1                               |

|                            |                           |
|----------------------------|---------------------------|
| <b>ScrewLocation??</b>     | 0.210 in                  |
| <b>WidthTolerance</b>      | +0.003 in / -0.010 in     |
| <b>SeatingTorque</b>       | 8 lb-in                   |
| <b>FinishSpecification</b> | Bright No Plating         |
| <b>BoreStyle</b>           | Right Threaded (Standard) |
| <b>Style</b>               | Clamp                     |
| <b>ShaftTolerance</b>      | +0.0000 in / -0.0005 in   |
| <b>FasteningDimensions</b> | Inch                      |
| <b>ISO 9001 (2008)</b>     | Yes                       |
| <b>REACH</b>               | Yes                       |
| <b>ROHS2</b>               | Yes                       |
| <b>ConflictMinerals</b>    | Yes                       |
| <b>ThreadedBore(B)</b>     | #10 - 32 TPI              |
| <b>ThreadClass</b>         | 3B                        |
| <b>Merk</b>                | Ruland Manufacturing      |

## Beschrijving

TCL-3-32-SS Ruland Manufacturing Shaft collar

## Product URL

<https://aandrijftechniek.nl/product/tcl-3-32-ss-ruland-manufacturing-shaft-collar-ruland-manufacturing/>