

# TP HTD 2250 5M 15 GATES PowerGrip™ Twin Power™ Endless timing belts GATES

SKU: 7G2052250-15



## Specificaties

<b>Gewicht (kg/m)</b>	0.154
<b>Spoed (mm)</b>	5
<b>Hoogte riem (mm)</b>	5.7
<b>Breedte riem (mm)</b>	15
<b>Spoorlengte (mm)</b>	2250
<b>Materiaal riem</b>	Chloroprene
<b>Koordmateriaal</b>	Glass
<b>Eenheden</b>	pc
<b>Riemprofiel</b>	5M
<b>numberOfTeethZ</b>	450
<b>toothWidthMM</b>	2.1
<b>Gewicht (kg)</b>	0.154
<b>Omschrijving (EN)</b>	Gates® PowerGrip™ HTD™ Twin Power™ synchronous belts are designed to perform at high speeds and in extreme temperatures, with a larger tooth profile for increased performance capacity. They have nylon facing on both tooth sides to provide equal high load carrying capabilities between the sides. Fibreglass tensile cords provide high strength durability, excellent flex life, and high resistance to elongation. Neoprene body resists against wear from grime, grease, oil and moisture. Temperature Range: -30°C to +100°C (-22°F to +212°F).
<b>Minimale temperatuur (°C)</b>	-30

<b>Maximale temperatuur (°C)</b>	+100
<b>EAN-code</b>	5414465740220
<b>Aangepaste code</b>	4010.3900.90
<b>Status</b>	Normal
<b>oringColour</b>	Black
<b>Land van herkomst</b>	GB
<b>beltBackSide</b>	Notched
<b>Tandvorm</b>	HTD Design
<b>sided</b>	Double Sided
<b>StatConductive</b>	No
<b>fabricMaterial</b>	Nylon
<b>beltEnd</b>	Endless
<b>sprockCompatible</b>	PowerGrip HTD
<b>Merk</b>	GATES
<b>Gewicht (kg/m)</b>	0.154
<b>Spoed (mm)</b>	5
<b>Breedte riem (mm)</b>	15
<b>Materiaal riem</b>	Chloroprene
<b>Riemprofiel</b>	5M
<b>Gewicht (kg)</b>	0.154
<b>Minimale temperatuur (°C)</b>	-30
<b>Maximale temperatuur (°C)</b>	+100
<b>Land van herkomst</b>	GB

## Beschrijving

TP HTD 2250 5M 15 GATES PowerGrip™ Twin Power™ Endless timing belts

## Product URL

<https://aandrijftechniek.nl/product/tp-htd-2250-5m-15-gates-powergrip-twin-power-endless-timing-belts-gates/>