

TP HTD 2350 5M 25 GATES PowerGrip™ Twin Power™ Endless timing belts GATES

SKU: 7G2052350-25



Specificaties

Gewicht (kg/m)	0.298
Spoed (mm)	5
Hoogte riem (mm)	5.7
Breedte riem (mm)	25
Spoorlengte (mm)	2350
Materiaal riem	Chloroprene
Koordmateriaal	Glass
Eenheden	pc
Riemprofiel	5M
numberOfTeethZ	470
toothWidthMM	2.1
Gewicht (kg)	0.298
Omschrijving (EN)	Gates® PowerGrip™ HTD™ Twin Power™ synchronous belts are designed to perform at high speeds and in extreme temperatures, with a larger tooth profile for increased performance capacity. They have nylon facing on both tooth sides to provide equal high load carrying capabilities between the sides. Fibreglass tensile cords provide high strength durability, excellent flex life, and high resistance to elongation. Neoprene body resists against wear from grime, grease, oil and moisture. Temperature Range: -30°C to +100°C (-22°F to +212°F).
Minimale temperatuur (°C)	-30

Maximale temperatuur (°C)	+100
EAN-code	5414465084065
Aangepaste code	4010.3900.90
Status	Normal
oringColour	Black
Land van herkomst	GB
beltBackSide	Notched
Tandvorm	HTD Design
sided	Double Sided
StatConductive	No
fabricMaterial	Nylon
beltEnd	Endless
sprockCompatable	PowerGrip HTD
Merk	GATES
Gewicht (kg/m)	0.298
Spoed (mm)	5
Breedte riem (mm)	25
Materiaal riem	Chloroprene
Riemprofiel	5M
Gewicht (kg)	0.298
Minimale temperatuur (°C)	-30
Maximale temperatuur (°C)	+100
Land van herkomst	GB

Beschrijving

TP HTD 2350 5M 25 GATES PowerGrip™ Twin Power™ Endless timing belts

Product URL

<https://aandrijftechniek.nl/product/tp-htd-2350-5m-25-gates-powergrip-twin-power-endless-timing-belts-gates/>