

# WSP-20-SS Ruland Manufacturing Shaft collar Ruland Manufacturing

SKU: 610WSP20SS



## Extra afbeelding



## Specificaties

|                        |                                 |
|------------------------|---------------------------------|
| Gewicht (kg)           | 0.263                           |
| boreType               | Round                           |
| OriginalType           | Shaft Collar - Double Wide      |
| SteelMaterial          | 303 Stainless Steel             |
| UNSPSCcode             | 31162811                        |
| MaterialSpecification  | 303 Stainless Steel             |
| ScrewType              | 18-8 300 Series Stainless Steel |
| ScrewFinish            | Bright                          |
| UPC                    | 634529136775                    |
| TariffCode             | 8483.60.8000                    |
| boreB1Inch             | 1.25                            |
| outsideDiameterInInput | 2.0625                          |
| widthWInchInput        | 1.0625                          |
| ClearanceDiameterInch  | 2.295                           |
| ForgedClampScrew       | 1/4-28                          |

|                            |                           |
|----------------------------|---------------------------|
| <b>NumberofScrewsEa</b>    | 4                         |
| <b>ScrewLocation??</b>     | 0.828 in                  |
| <b>WidthTolerance</b>      | +0.003 in / -0.010 in     |
| <b>BoreTolerance</b>       | +0.0020 in / +0.0005 in   |
| <b>SeatingTorque</b>       | 110 lb-in                 |
| <b>FinishSpecification</b> | Bright No Plating         |
| <b>BoreStyle</b>           | Round                     |
| <b>Style</b>               | Clamp                     |
| <b>ShaftTolerance</b>      | +0.0000 in / -0.0005 in   |
| <b>FasteningDimensions</b> | Inch                      |
| <b>ISO 9001 (2008)</b>     | Yes                       |
| <b>REACH</b>               | Yes                       |
| <b>ROHS2</b>               | Yes                       |
| <b>ConflictMinerals</b>    | Yes                       |
| <b>RecommendedGap</b>      | 0.063 in                  |
| <b>Bore(B2)</b>            | 1.2500 in                 |
| <b>MomentofInertia</b>     | 0.4215 lb-in <sup>2</sup> |
| <b>Merk</b>                | Ruland Manufacturing      |

## Beschrijving

WSP-20-SS Ruland Manufacturing Shaft collar

## Product URL

<https://aandrijftechniek.nl/product/wsp-20-ss-ruland-manufacturing-shaft-collar-ruland-manufacturing/>